china

enook

5000 cycles 3.2v 230ah lifepo4 battery LFP 3.2v 280ah lithium ion battery Grade A cells for Energy Storage



Product Specification

Basic Information

• Place of Origin:

· Model Number:

• Brand Name:

- Standard Rating Cycle: 2000 (0.5C/0.5C)
- 4000 Cycles (25)、2000 Cycles 45 • Cycling Performance:
- Charging Temperature: 0 ~65
- Standard Charge-0.5C(P) discharge Rate:
- Capacity: Customized
- -35 ~65 • Discharging Temperature:
- Weight: 1920±100G
- Battery Type: 3.2V 100Ah Lifepo4 Battery
 - 5000 cycles 3.2v 230ah lifepo4 battery, Energy Storage 3.2v 230ah lifepo4 battery



More Images

• Highlight:



Product Description:

With its impressive cycling performance, this battery pack can last up to 4000 cycles at 25 and up to 2000 cycles at 45, making it a reliable and durable power source for your electric bike. Additionally, its capacity is customizable to fit your specific needs. The LifePo4 Lithium Ion Battery also boasts a standard rating cycle of 2000 (0.5C/0.5C), ensuring that it provides consistent and stable power to your electric bike. And with a storage temperature range of 0 to 35, this battery pack can handle a variety of weather conditions.

Don't settle for anything less than the best for your Hailong electric bike battery. Choose the LifePo4 Lithium Ion Battery and experience reliable, long-lasting power for your 60v battery pack.

<section-header><section-header>

Lifepo4 battery 3.2V 304A



Automated



Ultra-Safe



Customized **Custom-made**



Environmentally Friendly

Product

Stable

Product Advantages

Stable Advantages Low IR / High CR / Discharge Steadily / Environmentally Friendly/Super Long



Features:

Product Name: LifePo4 Lithium Ion Battery Size: 118.5(H)*160(W)*50.1(T) Standard Charge-discharge rate: 0.5C(P) Standard Rating Cycle: 2000 (0.5C/0.5C) Discharging Temperature: -35 ~65 OEM/ODM: Yes(Accepted)

100% NEW A-grade Cells Lithium E-bike battery for electric bike/mountain bike/motorcycle/bicycle Available sizes: 60v 15Ah 20ah 30ah 40ah 45ah 50ah 60ah

Model List & Parameters

Model	Voltage (V)	Capacity (Ah)	Cycles (Ah)	Initial IR (≤mΩ)	Weight (g)	Height (mm)	Width (mm)	Thickness (mm)
Lf32	3.20	32	3500 (0.5C/0.5C)	1.5	730±50	94.3±0.5	148.3±0.8	26.7±0.5
LF50F	3.20	50	1500 (0.5C/0.5C)	2.0	1035±100	129.8±0.5	148.3±0.5	26.7±0.5
LF90K	3.20	90	6000 (1c/1C)	0.5	1994 <u>±</u> 50	200.5±0.5	130.3 <u>±</u> 0.3	36.7±0.5
LF100MA	3.20	101	2000 (0.5C/0.5C)	0.5	1920±100	118.5 <u>±</u> 0.5	160.0±0.8	50.1±0.5
LF100LA	3.20	102	5000 (0.5C/0.5C)	0.5	1985±100	118.5±0.5	160.0±0.8	50.1±0.5
Lf105	3.20	105	4000 (0.5C/0.5C)	0.32	1980±60	200.5±0.5	130.3±0.5	36.35±0.5
Lf160	3.20	160	4000 (0.5C/0.5C)	0.21	3000±100	153.5±0.5	173.9±0.5	53.85±0.5
Lf173	3.20	173	4000 (0.5C/0.5C)	0.25	3190 <u>+</u> 96	207.5±0.5	173.9±0.5	41.06±0.5
Lf230	3.20	230	4000 (0.5C/0.5C)	0.2	4140±124	207.2 <u>±</u> 0.5	173.9 <u>±</u> 0.5	53.85 <u>+</u> 0.5
LF280K	3.20	280	6000 (0.5C/0.5C)	0.25	5420±300	207.2±0.5	173.7+0.5	72.0+1.0
Lf304	3.20	304	4000 (0.5C/0.5C)	0.16	5450±164	207.2 <u>±</u> 0.5	173.7±0.5	71.70.8

Product

Advantages



Technical Parameters:

Size	118.5(H)*160(W)*50.1(T)		
Cycling Performance	4000 Cycles (25),2000 Cycles(45)		
Package	ABS/Metal Case Or OEM		
Discharging Temperature	-35 ~65		

Storage Temperature	0~35
Voltage	Customized
Capacity	Customized
Weight	1920±100G
Standard Rating Cycle	2000 (0.5C/0.5C)
Standard Charge-discharge rate	0.5C(P)

This is a removable battery for e-bike that is made with 100% NEW A-grade Cells.



Applications:

The enook 3.2V Lifepo4 Lithium lon Battery is designed to be used in a variety of different scenarios. It is perfect for use in electric vehicles, such as electric bikes and scooters, as well as for use in solar power systems. It can also be used in backup power systems for homes and businesses, as well as for use in industrial applications.

The enook 3.2V Lifepo4 Lithium Ion Battery has an excellent cycling performance, with 4000 Cycles (25) and 2000 Cycles(45). This means that the battery can be charged and discharged repeatedly without losing its performance. It also has a wide charging temperature range of 0~65 and a discharging temperature range of -35~65, making it suitable for use in a variety of different environments. The enook 3.2V Lifepo4 Lithium Ion Battery is available in a range of different sizes and weights, from approximately 4.0~40.0kg, making it suitable for use in a variety of different applications. It can also be used to create a 60v battery pack, which is ideal for use in electric vehicles and other high-power applications.

In summary, the enook 3.2V Lifepo4 Lithium Ion Battery is a high-quality and versatile battery that is perfect for use in a variety of different scenarios. With its excellent cycling performance, wide temperature range, and customizable voltage, it is the ideal choice for anyone looking for a reliable and long-lasting battery.

Product Advantages

Our products have a very widely range of use



Customization:



Stable

Product Advantages

Low IR / High CR / Discharge Steadily / Environmentally Friendly/Super Long



Lifepo4 battery 3.2V 304A

Product Advantages



Automated



Customized Custom-made

Ultra-Safe



Super Long



Stable



Environmentally Friendly



Support and Services:

The LifePo4 Lithium Ion Battery is a high-performance rechargeable battery designed for various applications such as electric vehicles, solar energy storage systems, and portable electronic devices. Our product technical support and services include:

- Technical consultation: Our team of experts is available to provide technical consultation and support to help you choose the right battery for your application and answer any technical questions you may have.

- Custom battery design: We offer custom battery design services to meet your specific requirements and application needs.

- Battery testing and certification: Our batteries are rigorously tested and certified to ensure that they meet the highest quality and safety standards.

- Battery maintenance and repair: We provide battery maintenance and repair services to help you prolong the life of your battery and ensure its optimal performance.

- Warranty and support: We stand behind the quality of our products and offer warranty and support services to ensure your satisfaction with our products.



Packing and Shipping:

Product Packaging:

The LifePo4 Lithium Ion Battery will be packaged in a sturdy cardboard box with cushioning to protect it during shipping. The box will also include a user manual and any required cables or accessories. Shipping:

The battery will be shipped via a reputable courier service to ensure safe and timely delivery. Shipping costs will be calculated based on the destination and shipping method selected at checkout. International shipping may be subject to customs fees and import duties, which are the responsibility of the buyer.

PACKAGING

Product Advantages









Shipping by



Professional suggestion to choose the best shipping delivery (Such as EMS DHL TNT UPS and FEDEX) for your commodities according to your demand.

Company Introduction

ChangSha Enook Technology Co., Ltd located is an outstanding solution service provider in Lithium Battery Management System(BMS) industry, focusing on the R&D, design, production and sales of Apexium DIY kits, BMS and battereis for more than 15 years. With its strength, it can provide customers with first-class software and hardware devel- opment and after-sales services.

Quality first is our principle,Satisfying all our customers is ourtenet,win-win business is our aim.Dedicated to strict qualitycontrol and thoughtful customer service,our experiencedstaff members are always available to discuss eachdetailed requirements from customer and ensure fullcustomer satisfaction. In addition, we have obtained certificates. MSDS UN38.3MSDS, ROHS, UL.ect. All our products keep selling wellnot onlyaround China, but also inUSA, Philippines, Germany, EnglandAustralia, Russia, France and other Europen and Asia countries Fast delivery is one of our advantage, selecting a current products from catalogue, or customized products, 3[~]5 days is the normal time to prepare for the goods, OEM & ODM orders can be acceptable.

Please don't hesitate to contact us if you have any requirement, we'll provideour best service to you.

Our Factory













Company Exhibition















endigend Libert Footherogy Col, Ltd
+8617752866093 Swendy@enooktech.com enookbattery.com
ROOM 1717, JIEZUO BUILDING, NO. 828, SECTION 1, FURONG SOUTH ROAD, TIANXIN DISTRICT, CHANGSHA, HUNAN